

Contents

Page

Foreword	vii
Rotodynamic (centrifugal) pumps	1
1.1 Types and nomenclature	1
1.1.1 Scope	1
1.1.2 Definition of rotodynamic (centrifugal) pumps	1
1.1.3 Types of rotodynamic pumps	1
1.1.4 Impeller designs	7
1.1.5 Construction drawings	9
1.1.6 General information	38
1.1.7 Centrifugal pumps nomenclature	43
1.2 Definitions	61
1.2.1 Rate of flow (Q) [Q]	63
1.2.2 Speed (n)	64
1.2.3 Head (h) [H]	64
1.2.4 Condition points	66
1.2.5 Suction conditions	66
1.2.6 Power	67
1.2.7 Pump pressures	68
1.2.8 Impeller balancing	69
1.2.9 Rotodynamic pump icons	69
Appendix A References	78
Appendix B Standard Dimension for HI – NEMA Type C Face-Mounted Motors	79
Appendix C Index	86
Figures	
Figure 1.1.3a — Rotodynamic pump types - overhung	2
Figure 1.1.3b — Rotodynamic pump types - between bearings	3
Figure 1.1.3c — Rotodynamic pump types - vertically suspended	4
Figure 1.1.3d — Rotodynamic pump types - regenerative turbine	4
Figure 1.1.4.1 — General impeller types	8
Figure 1.1.4.2 — Double suction radial flow pump	9
Figure 1.1.4.3 — Mixed flow impeller	9
Figure 1.1.4.4 — Axial flow impeller	9
Figure 1.1.5a — Overhung impeller – flexibly coupled – single stage – frame mounted	10
Figure 1.1.5b — Overhung impeller – flexibly coupled – single stage – frame mounted – lined pump	11
Figure 1.1.5c — Stock pump – flexibly coupled – single stage – foot mounted	12
Figure 1.1.5d — Overhung impeller – flexibly coupled – single stage – foot mounted – mixed flow	13
Figure 1.1.5e — Overhung impeller – flexibly coupled – single stage – foot mounted – ANSI B73.1	14
Figure 1.1.5f — Overhung impeller – flexibly coupled – single stage – foot mounted – self-priming	15
Figure 1.1.5g — Overhung impeller – flexibly coupled – single stage – centerline mounted – API 610	16
Figure 1.1.5h — Overhung impeller – integral bearing frame – single stage – in-line – flexible coupling	17
Figure 1.1.5i — Vertical end suction OH3A	18
Figure 1.1.5j — Overhung impeller – rigidly coupled – single stage – vertical in-line	19

Figure 1.1.5k — Overhung impeller – close coupled – single stage – in-line (showing seal and packing)	20
Figure 1.1.5l — Vertical end suction OH5A – close coupled – built together.	21
Figure 1.1.5m — High speed – integral gear – close coupled – single stage	22
Figure 1.1.5n — Overhung impeller – close coupled – single stage – end suction	23
Figure 1.1.5o — Overhung impeller – close coupled – single stage – diffuser style – end suction – submersible	24
Figure 1.1.5p — Overhung impeller – close coupled – single stage – volute style – end suction submersible	25
Figure 1.1.5q — Overhung impeller – flexibly coupled – single stage – axial flow – horizontal.	26
Figure 1.1.5r — Lineshaft design sump pump	27
Figure 1.1.5s — Cantilever shaft design sump pump	28
Figure 1.1.5t — Impeller between bearings – flexibly coupled – single stage – axial (horizontal) split case.	29
Figure 1.1.5u — Impeller between bearings – flexibly coupled – single stage – radial split case	30
Figure 1.1.5v — Impeller between bearings – flexibly coupled – multistage axial (horizontal) split case	31
Figure 1.1.5w — Impeller between bearings – flexibly coupled – multistage – radial split case	32
Figure 1.1.5x — Impeller between bearings – flexibly coupled – multistage – radial split-double casing	33
Figure 1.1.5y — Regenerative turbine – side channel single stage.	34
Figure 1.1.5z — Regenerative turbine – peripheral single stage.	35
Figure 1.1.5aa — Regenerative turbine – impeller between bearings – two stage	36
Figure 1.1.5bb — Pitot pump – flexibly coupled – single stage – frame mounted	37
Figure 1.1.6.5.1.1 — Liquid end (or wet end) assembly	39
Figure 1.1.6.5.1.2 — Power end (or frame assembly)	40
Figure 1.1.6.5.1.3 — Back pull-out assembly	40
Figure 1.1.6.6 — Position of casing and shaft rotation	41
Figure 1.1.6.7a — Horizontal pump – shaft rotation (CW rotation)	42
Figure 1.1.6.7b — Vertical pump – shaft rotation (CW rotation)	42
Figure 1.1.6.8 — Pump with C-frame motor adapter, short coupled	43
Figure 1.1.7.2a — Overhung impeller – flexibly coupled – single stage – frame mounted	55
Figure 1.1.7.2b — Overhung impeller – flexibly coupled – single stage – frame mounted – pump on baseplate	55
Figure 1.1.7.2c — Overhung impeller – flexibly coupled – single stage – centerline mounted	56
Figure 1.1.7.2d — Overhung impeller – flexibly coupled – single stage – centerline mounted – pump on baseplate	56
Figure 1.1.7.2e — Overhung impeller – flexibly coupled – single stage – centerline mounted (top suction).	57
Figure 1.1.7.2f — Overhung impeller – flexibly coupled – single stage – centerline mounted – pump on baseplate (top suction)	57
Figure 1.1.7.2g — Impeller between bearings – flexibly coupled – single stage – axial (horizontal) split case – pump on baseplate	58
Figure 1.1.7.2h — Impeller between bearings – flexibly coupled – single stage – axial (horizontal) split case.	58
Figure 1.1.7.2i — Overhung impeller – close coupled – single stage – end suction	59
Figure 1.1.7.2j — Overhung impeller – separately coupled – single stage – frame mounted (vertically mounted)	59
Figure 1.1.7.2k — Overhung impeller – integral bearing frame – single stage – vertical end suction with flexible coupling	60
Figure 1.1.7.2l — Overhung impeller close coupled – single stage – vertical end suction	60
Figure 1.2.3.4 — Datum elevation for various pump designs at eye of first-stage impeller.	65
Figure 1.2.9.1.1 — Pump type OH00: Horizontal, flexibly coupled, axial flow, single stage, overhung design.	69
Figure 1.2.9.1.2 — Pump type OH0: Horizontal, frame mounted, flexibly coupled, single stage, overhung design	70
Figure 1.2.9.1.3 — Pump type OH1: Horizontal, foot mounted, single stage, overhung design	70

Figure 1.2.9.1.4 — Pump type OH2: Horizontal, centerline mounted, single stage, overhung design	70
Figure 1.2.9.1.5 — Pump type OH3: Vertical, in-line mounted, single stage, with integral bearing bracket.	71
Figure 1.2.9.1.6 — Pump type OH4: Vertical, in-line mounted, single stage, rigidly coupled to the driver shaft	71
Figure 1.2.9.1.7 — Pump type OH5: Vertical, in-line mounted, single stage, close coupled to the driver shaft	72
Figure 1.2.9.1.8 — Pump type OH6: High-speed, integral gear driven, single stage, overhung design.	72
Figure 1.2.9.1.9 — Pump types OH8A and OH8B.	73
Figure 1.2.9.1.10 — Pump types OH9, OH10, OH11, and OH12	73
Figure 1.2.9.2.1 — Pump type BB1: Horizontal, axial split, single and two stage, between-bearings design.	73
Figure 1.2.9.2.2 — Pump type BB2: Horizontal, radial split, single and two stage, between-bearings design.	74
Figure 1.2.9.2.3 — Pump type BB3: Horizontal, axial split, multistage, between-bearings design	74
Figure 1.2.9.2.4 — Pump type BB4: Horizontal, radially split, multistage, between-bearings design.	74
Figure 1.2.9.2.5 — Pump type BB5: Horizontal, radially split, multistage, double casing, between-bearings design	75
Figure 1.2.9.3.1 — Pump type VS4: Vertical, single volute casing, lineshaft, flexibly coupled to the driver.	75
Figure 1.2.9.3.2 — Pump type VS5: Vertical, single volute casing, stiff-shaft cantilever, flexibly coupled to the driver	76
Figure 1.2.9.4.1 — Pump type RT1: Overhung, close-coupled, side channel design.	76
Figure 1.2.9.4.2 — Pump type RT2: Overhung, close-coupled, peripheral design.	76
Figure 1.2.9.4.3 — Pump type RT3: Between-bearing, flexibly coupled, side channel design.	77
Figure 1.2.9.4.4 — Pump type RT4: Between-bearing, flexibly coupled, peripheral design.	77
Figure 1.2.9.5.1 — Pitot (rotating casing) pumps	77
Figure B.1 — Dimensions for types JM and JP, alternating current, face-mounting, close-coupled pump motors having rolling element contact bearings.	81
Figure B.2 — Standard dimensions for HI - NEMA type HP and HPH vertical, solid-shaft motors	85
Tables	
Table 1.1.3.1 — Overhung rotodynamic pump attributes	6
Table 1.1.7.1a — Centrifugal pump nomenclature – alphabetical listing.	44
Table 1.1.7.1b — Centrifugal pump nomenclature – numerical listing.	52
Table 1.2a — Principal symbols	61
Table 1.2b — Subscripts	63
Table B.1 — Dimensions for type JM, alternating current, face-mounting, close-coupled pump motors (US customary units).	80
Table B.2 — Dimensions for type JP, alternating current, face-mounting, close-coupled pump motors (US customary units).	82
Table B.3 — Open drip-proof frame selections	83
Table B.4 — Standard dimensions for HI - NEMA type HP and HPH vertical solid-shaft motors (US customary units).	84