

Contents

Page

Foreword	v
11.6 Submersible pump tests	1
11.6.1 Test	1
11.6.2 Types of tests	1
11.6.3 Terminology	1
11.6.4 Performance test	7
11.6.5 Hydrostatic test	10
11.6.6 Net positive suction head (NPSH) test	12
11.6.7 Submersible motor integrity tests	15
11.6.8 Vibration test	18
11.6.9 Instrumentation	18
11.6.10 Model tests	27
Appendix A Formulas and Examples	28
A.1 Affinity laws (centrifugal pumps)	28
A.2 Calculated performance based on change in pump speed (metric)	29
A.3 Calculated performance based on change in pump impeller diameter (US units)	29
A.4 Calculation of NPSHA on a wet-pit pump (metric)	30
A.5 Calculation of NPSHA on a dry-pit pump (US units)	30
A.6 Calculation of performance ranges based on level A and level B acceptance criteria performance tolerances (US units)	31
Appendix B Standards-Setting Organizations	32
Appendix C Index	34
Figures	
11.6.1 Datum elevation for horizontal pumps	4
11.6.2 Datum elevation for vertical pumps	4
11.6.3 Wet pit performance test setup	7
11.6.4 Dry pit performance test setup	8
11.6.5 Pump performance (data plotted at test speed)	11
11.6.6 Hydrostatic pressure test setup	11
11.6.7 Suction throttling NPSH test setup	12
11.6.8 Variable-lift NPSH test setup	13
11.6.9 Closed-loop dry pit NPSH test setup	13
11.6.10 Closed-loop wet pit NPSH test setup	14

11.6.11 NPSH test with flow rate held constant.	14
11.6.12 NPSH test with suction head held constant	15
11.6.13 Submersible motor integrity test setup using housing pressure check method	16
11.6.14 Submersible motor integrity test setup using the housing vacuum check method	17
11.6.15 Transducer location	19
11.6.16A Vibration limits (metric)	20
11.6.16B Vibration limits (US units)	20
11.6.17 Typical pressure tap or orifice.	25
11.6.18 Typical pressure tap arrangement	25
11.6.19 Gauge connectors.	26

Tables

11.6.1 Symbols	2
11.6.2 Subscripts	3
11.6.3 Total head tolerance at specified flow rate	9
11.6.4 Flow rate tolerance at specified total head	10
11.6.5 Efficiency tolerance at specified flow rate	10
11.6.6 Fluctuation and inaccuracy limits	21
11.6.7 Maximum instrument calibration interval.	21
11.6.8 Straight pipe required before a venturi meter in diameters of pipe	22
11.6.9 Straight pipe required before a nozzle or orifice plate in diameters of pipe	23
11.6.10 Straight pipe downstream of pressure tap of a nozzle or orifice plate meter in diameters of pipe	23