

Contents

Page

Foreword	vii
12 Rotodynamic (centrifugal) slurry pumps	1
12.0 Scope	1
12.1 Objective	1
12.1.1 Introduction	1
12.1.2 Pump types and nomenclature	1
12.1.3 Definition of slurry	3
12.1.4 Definition of slurry pumps	3
12.1.5 Overhung impeller	4
12.1.6 Frame mounted	4
12.1.7 Cantilevered wet pit	4
12.1.8 Submersible	4
12.1.9 Lined type	4
12.1.10 Unlined type	4
12.1.11 Construction drawings	4
12.1.12 Part names	4
12.1.13 Letter dimensional designations	28
12.2 Definitions	31
12.2.1 Rate of flow (Q)	33
12.2.2 Speed (n)	33
12.2.3 Head (h)	33
12.2.4 Condition points	35
12.2.5 Suction conditions	36
12.2.6 Power	36
12.2.7 Pump pressures	37
12.2.8 Mechanical seal terms	38
12.2.9 Slurry terminology	39
12.3 Design and application	44
12.3.1 Scope	44
12.3.2 Slurry services	44
12.3.3 Froth pumping	52
12.3.4 Wear in centrifugal slurry pumps	55
12.3.5 Hydraulic design and application considerations	60
12.3.6 System design	62
12.3.7 Wetted materials of construction	63
12.3.8 General arrangement details	66
12.3.9 Drive train arrangements	82
12.4 Installation, operation, and maintenance	83
12.4.1 Installation	83
12.4.2 Nozzle loads	83
12.4.3 Connecting piping	89
12.4.4 Commissioning	89
12.4.5 Start-up	89
12.4.6 Storage of elastomer linings	90
12.4.7 Impeller removal	90
12.4.8 Axial adjustment of the bearing housing	90

12.4.9	Piping system design	90
12.4.10	Possible operating problems	91
12.4.11	Spare parts stock	92
12.4.12	Maintenance procedures for maximum part life	92
12.4.13	Operational considerations	93
12.5	Intentionally left blank	93
12.6	Testing	93
12.6.1	Scope	93
12.6.2	Test conditions	94
12.6.3	Manufacturer's testing	94
12.6.4	Field tests	94
12.6.5	Wear tests	94
12.6.6	Instrumentation	95
Appendix A	Equipment data sheets (informative)	96
Appendix B	Source material and references (informative)	101
B.1	Source material	101
B.2	References	102
B.3	Standards organizations	103
Appendix C	Nozzle load tables (informative)	104
Appendix D	Materials data (informative)	106
D.1	Metal specification equivalents	106
D.2	Specific gravity of various materials	107
Appendix E	Index (informative)	109
 Figures		
12.1.2a	— Rotodynamic (centrifugal) slurry pump types	2
12.1.4	— Typical material types and discharge pressure for particle size	3
12.1.2b	— Overhung impeller, separately coupled, single-stage, frame-mounted, metal-lined pump (OH0)	5
12.1.2c	— Overhung impeller, separately coupled, single-stage, frame-mounted, elastomer-lined pump (OH0)	6
12.1.2d	— Overhung impeller, separately coupled, single-stage, frame-mounted, elastomer-lined pump, adjustable sideliners (OH0)	7
12.1.2e	— Overhung impeller, separately coupled, single-stage, frame-mounted, end suction, vulcanized-elastomer-lined pump (OH0)	8
12.1.2f	— Overhung impeller, separately coupled, single-stage, frame-mounted, end suction, metal, unlined casing pump (OH0)	9
12.1.2g	— Overhung impeller, separately coupled, single-stage, frame-mounted, side inlet, metal, unlined casing pump (OH0)	10
12.1.2h	— Overhung impeller, separately coupled, single-stage, frame-mounted, end suction, metal, tie bolt plate construction pump (OH0)	11
12.1.2i	— Overhung, open impeller, separately coupled, single-stage, frame-mounted, metal, ASME B73.1 type pump (OH1)	12
12.1.2j	— Overhung impeller, separately coupled, single-stage, wet pit cantilever, elastomer-lined, single suction pump (VS5)	13

12.1.2k — Overhung impeller, separately coupled, single-stage, wet pit cantilever, elastomer, vulcanized-lined, double suction pump (VS5)	14
12.1.2l — Overhung impeller, separately coupled, single-stage, wet pit cantilever, unlined, metal, single suction pump (VS5)	15
12.1.2m — Overhung impeller, close-coupled, single-stage, submersible, elastomer-coated, single suction pump (OH8B)	16
12.1.2n — Overhung impeller, close-coupled, single-stage, submersible, elastomer-lined, single suction pump (OH8B)	17
12.1.2o — Overhung impeller, close-coupled, single-stage, submersible, elastomer-lined, double suction pump (OH8B)	18
12.1.2p — Overhung impeller, close-coupled, single-stage, end suction, metal, submersible pump with agitator (OH8B)	19
12.1.2q — Overhung impeller, close-coupled, single-stage, submersible, metal, double suction pump (OH8B)	20
12.1.13a — Horizontal pump dimensions	28
12.1.13b — Direct drive pump and motor assembly dimensions.	29
12.1.13c — Vertical pump dimension	30
12.2.3.4 — Datum elevations for various slurry pump designs	34
12.2.9.4 — Schematic classification of slurries in industrial pipeline applications	40
12.3.2.1 — Solids transport rate	46
12.3.2.2 — Nomograph for the relationship of concentration to specific gravity in aqueous slurries.	47
12.3.2.4 — Nomograph for maximum velocity at limit of stationary deposition of solids.	49
12.3.2.5 — Effect of settling slurry on pump characteristics (schematic).	50
12.3.2.7 — Effect of average particle size and impeller diameter on H_r and R_h	51
12.3.3 — Application of froth factor to pump selection	54
12.3.4.1a — Wear coefficient W_c for different resisting materials in a neutral pH media for different average-sized abrading particles	57
12.3.4.1b — Erosion response for different impingement angles and materials	58
12.3.4.2a — Service class chart for slurry pump erosive wear	59
12.3.4.2b — Miller number versus material abrasivity.	60
12.3.6 — Typical constant concentration slurry pipeline friction loss characteristics.	62
12.3.8.2a — Typical lip seal and its components.	67
12.3.8.2b — Typical labyrinth seal.	68
12.3.8.2c — Generic bearing isolator and its major components	68
12.3.8.3.1a — “Flush-type” stuffing box with lantern ring in standard position	70
12.3.8.3.1b — “Weep-type” stuffing box with lantern ring	70
12.3.8.3.1c — Flow through flush	71
12.3.8.3.6 — Centrifugal (dynamic) seal with “dry-type” packing.	73
12.3.8.3.7 — Multiple elements lip seal with internal flush.	74
12.3.8.3.8a — Flow rates required to create 4.6 m/s (15 ft/s) velocity past a bushing	76
12.3.8.3.8b — Slurry pump shaft alignment and runout	78
12.3.8.3.8c — Dual pressurized seal arrangement for slurry applications.	78
12.3.8.3.9a — Rotating elastomeric bellows seal	78

12.3.8.3.9b — Stationary elastomeric bellows seal	79
12.3.8.3.9c — Heavy-duty slurry seal with quench device.	79
12.3.8.3.9d — Heavy-duty slurry seal with elastomeric liner	80
12.3.8.3.9e — Fully split nonpusher seal.	80
12.3.8.3.9f — Specialty slurry seal	81
12.4.2 — Direction of forces and moments being applied to suction and discharge nozzles	83
12.4.2.7a — Sliding movement when forces and moments are transferred to pump feet.	86
12.4.2.7b — Forces and moments applied to pumps with various suction and discharge nozzle locations	87
12.4.2.9 — Bolts in tension when a moment is applied to the pump	88
Tables	
12.1.12a — Slurry pump nomenclature – alphabetical listing	21
12.1.12b — Slurry pump nomenclature - numerical listing	27
12.2a — Principal symbols	31
12.2b — Subscripts	32
12.3.2.7 — Specific gravity correction factor	51
12.3.3 — Approximate froth factors	53
12.3.5a — Recommended service limitations for acceptable wear	61
12.3.5b — Acceptable range of relative flow rates for slurry pump casing optimum wear.	62
12.3.7.1 — General suitability of wetted materials.	63
12.3.8.2 — Calculated fatigue life of bearings by slurry service class	69
12.3.8.3.8 — Application limits of single mechanical seals	75
12.3.8.3.10 — Recommended water quality limits.	81
12.4.2.9 — Calculation of allowable forces and moments on the suction(s) and discharge(d) connections	88
C.1 — Typical allowable combined nozzle loads for centrifugal end suction slurry pumps – metric	104
C.2 — Typical allowable combined nozzle loads for centrifugal end suction slurry pumps – US customary units	105