

Contents

Page

Foreword	v
9.6.6 Pump piping for rotodynamic pumps	1
9.6.6.1 Objective	1
9.6.6.2 Introduction	1
9.6.6.3 Inlet (suction) piping requirements	1
9.6.6.3.1 Inlet (suction) pipe size/velocity requirements	2
9.6.6.3.2 Effect of piping-generated swirl	2
9.6.6.3.3 Required straight pipe lengths	4
9.6.6.4 Inlet and outlet general piping requirements	4
9.6.6.4.1 Pipe nozzle alignment/pipe expansion load	4
9.6.6.4.2 Pipe supports/anchors	6
9.6.6.4.3 Parallel operation	7
9.6.6.5 Outlet (discharge) piping requirements	9
9.6.6.5.1 Pipe size/velocity requirements	9
9.6.6.5.2 Required straight pipe lengths	9
9.6.6.5.3 Recommended valves	9
9.6.6.5.4 Water hammer	10
9.6.6.6 References	10
9.6.6.7 Sources of additional information	11
9.6.6.8 List of acronyms	11
Appendix A System Curves	13
A.1 Calculation of the system curve	13
A.2 Pipe head loss calculation methods	15
Appendix B Water Hammer	17
B.1 Water hammer	17
Appendix C Selecting and Locating Pipe Supports and Restraints	21
C.1 Restraint and stops	21
C.2 Pipe supports for vertical loads	21
C.3 Guides and restraints	23
C.4 True anchors	23
C.5 Spring supports	23
C.6 Friction from supports	24
Appendix D Expansion Joints and Couplings	25
D.1 Expansion joint types	25
D.2 Expansion joint application	27
Appendix E Specialty Piping Components and Applications	29
E.1 Check valves and strainers	29
E.2 Devices to improve flow to the pump	30
E.3 Piping for suction lift applications	31
E.4 Solids/slurry	31

E.5	Air release valves	32
Appendix F	Discharge Pressure Pulsation and Acoustic Resonance	33
F.1	Discharge pressure pulsation/acoustic resonance	33
Appendix G	Index	35

Figures

9.6.6.3	— Suction pipe design	2
9.6.6.3.3a	— Pump installed with elbows	4
9.6.6.3.3b	— Undesirable effects of elbow directly on suction	5
9.6.6.4.3a	— Parallel pump installation	8
9.6.6.4.3b	— Constant-velocity manifold design, parallel pumps	8
9.6.6.4.3c	— Minimum required suction line lengths and spacing for parallel pumps	9
9.6.6.5.3	— Triple-duty valve	10
C.1	— Pipe supports for vertical loads	22
C.2	— Solid pipe hanger supports	22
C.3	— Constant-effort spring supports	22
C.4	— Pipe guides	23
C.5	— Spring supports	24
D.1	— Slip/packing expansion joint	25
D.2	— Rubber expansion joints	26
D.3	— Metal bellows expansion joint	26
D.4	— Expansion joint bolting arrangement	27
E.1	— Foot valve	29
E.2	— Typical temporary strainer	30
E.3	— Second upstream perpendicular elbow	30
E.4	— Self-priming bypass	31

Tables

9.6.6.3.2	— Minimum required straight pipe length (L2) before pump suction inlet	3
B.1	— Magnitude of pressure wave	20