

Table of Contents

| | |
|---|-------|
| Foreword | xi |
| Acknowledgements | xiii |
| About the Hydraulic Institute | xvii |
| Europump | xvii |
| Executive Summary | xix |
| What is Life Cycle Cost? | xx |
| Getting Started | xxi |
| Introduction | xxiii |

Chapter • One Life Cycle Cost, 1

| | |
|---|----|
| 1.1 General | 1 |
| 1.2 Elements of Life Cycle Costs | 3 |
| 1.2.1 Initial Cost (C_{ic}) | 3 |
| 1.2.2 Installation and Commissioning (Start-up) Cost (C_{in}) | 4 |
| 1.2.3 Energy Cost (C_e) | 5 |
| 1.2.4 Operating Cost (C_o) | 6 |
| 1.2.5 Maintenance and Repair Cost (C_m) | 6 |
| 1.2.6 Downtime and Loss of Production Cost (C_s) | 8 |
| 1.2.7 Environmental Cost, Including Disposal of Parts and Contamination from Pumped Liquid (C_{env}) | 8 |
| 1.2.8 Decommissioning and Disposal Cost, Including Restoration of the Local Environment (C_d) | 8 |
| 1.3 Calculating Life Cycle Costs | 9 |
| 1.3.1 General | 9 |
| 1.3.2 Calculating Present Value (PV) | 10 |
| 1.3.3 Calculation Chart Using the Simplified Method | 11 |
| 1.3.4 Example Using the Manual Calculation Chart | 14 |

Chapter • Two Pumping System Design, 17

| | |
|--|----|
| 2.1 General | 17 |
| 2.2 System Design | 17 |
| 2.2.1 Pipe Size | 17 |
| 2.2.2 Pump and System Curves | 18 |
| 2.3 Output Control | 20 |

| | | |
|-------|---|----|
| 2.4 | Pump Type Selection | 20 |
| 2.4.1 | Pump Types | 20 |
| 2.4.2 | Ways to Reduce LCC When Selecting Pumps | 28 |
| 2.5 | Selecting a Driver. | 36 |
| 2.5.1 | Background | 36 |
| 2.5.2 | Types of Electric Motors | 36 |
| 2.5.3 | Efficiency and Energy Costs | 38 |
| 2.5.4 | Variable Frequency Drives | 39 |
| 2.6 | Auxiliary Services. | 40 |
| 2.6.1 | Cooling Services | 40 |
| 2.6.2 | Heating | 41 |
| 2.6.3 | Seal Flush Systems. | 41 |
| 2.6.4 | Seal Quench Systems. | 42 |
| 2.6.5 | Barrier Fluid Systems | 42 |
| 2.6.6 | Lubrication Systems for Sleeve Bearings | 42 |
| 2.7 | Power Transmission | 42 |
| 2.7.1 | Summary of Power Transmission Characteristics. | 42 |
| 2.8 | System Effectiveness in Design and Output Control: A New Concept | 43 |
| 2.8.1 | Process Requirements | 43 |
| 2.8.2 | Specific Energy | 47 |
| 2.8.3 | Summary | 52 |
| 2.9 | Monitoring and Sustaining the System | 53 |
| 2.9.1 | Maintaining Pump Efficiency | 53 |
| 2.9.2 | Organizing Maintenance and Monitoring. | 60 |

Chapter • Three

Methods for Analyzing Existing Pumping Systems, 63

| | | |
|-------|---|----|
| 3.1 | Introduction | 63 |
| 3.2 | Improving the System | 63 |
| 3.3 | System Components | 64 |
| 3.3.1 | Pump | 64 |
| 3.3.2 | Control or Throttle Valves | 65 |
| 3.3.3 | Components | 65 |
| 3.4 | System Loads | 66 |
| 3.5 | Determining the Rates of Flow. | 66 |
| 3.6 | Example of Minimizing Losses by Balancing a Branched System. | 67 |
| 3.6.1 | Balancing the System | 67 |
| 3.6.2 | Changing the Pump. | 69 |

| | |
|--|----|
| 3.7 Examples for Achieving Energy Savings in Existing Systems | 71 |
| 3.7.1 Example 1: Waste Collection System With Oversized Pumps | 71 |
| 3.7.2 Example 2: System With a Problem Control Valve. | 75 |

Chapter • Four

Examples of LCC Analysis, 79

| | |
|---|----|
| 4.1 Waste Collection System Example | 79 |
| 4.2 Problem Control Valve Example | 80 |

Chapter • Five

Effective Procurement Using LCC, 91

| | |
|---|----|
| 5.1 Introduction | 91 |
| 5.2 Enquiry Documentation. | 91 |
| 5.3 Evaluation Sum. | 92 |
| 5.4 Work Methodology | 92 |
| 5.5 Contract Boundaries | 93 |
| 5.6 Evaluating Tenders | 93 |
| 5.7 Inspection - Performance Bonus or Penalty | 93 |
| 5.8 Example | 93 |

Chapter • Six

Recommendations for Designing and Procuring Pumping Systems, 95

Chapter • Seven

References, 99

Chapter • Eight

Glossary of Terms and Symbols, 103

Appendix A

System Curves, 105

| | |
|--------------------------------------|-----|
| A.1 System Curves | 105 |
| A.1.1 Operating Duty Point | 105 |

| | | |
|-------|---|-----|
| A.1.2 | Characteristic Curves | 105 |
| A.1.3 | Branched Piping Systems | 117 |
| A.1.4 | Duty Modifications | 121 |
| A.1.5 | Viscous and Non-Newtonian Liquids | 124 |
| A.2 | Computer Software | 125 |

Appendix B

Pumping Output and System Control, 127

| | | |
|-------|---|-----|
| B.1 | Output Control | 127 |
| B.1.1 | General. | 127 |
| B.1.2 | Determining Flow Requirements | 128 |
| B.2 | System Control | 131 |
| B.2.1 | Control Parameters | 132 |
| B.2.2 | Start–Stop Control | 134 |
| B.2.3 | Throttling Control | 137 |
| B.2.4 | Variable Speed Regulation. | 138 |
| B.2.5 | Eccentric Radius Adjustment in Vane Cell Pumps. | 141 |
| B.2.6 | Stroke and Speed Regulation of Reciprocating Positive Displacement Pumps | 141 |
| B.3 | Summary | 142 |

Appendix C

Pump Efficiencies, 145

| | | |
|-------|-----------------------------|-----|
| C.1 | Pump Efficiencies | 145 |
| C.1.1 | General. | 145 |
| C.1.2 | Nomenclature | 147 |

Appendix D

Case Histories–Cost Savings Examples, 149

| | | |
|-----|--|-----|
| D.1 | Introduction | 149 |
| | Case History 1: Building services. | 152 |
| | Case History 2: Pulp and paper manufacture. | 154 |
| | Case History 3: Chemical processing. | 156 |
| | Case History 4: Water supply. | 158 |
| | Case History 5: Waste water. | 160 |
| | Case History 6: Steel making. | 162 |
| | Case History 7: Petrochemical processing. | 164 |
| | Case History 8: Domestic electrical appliance. | 166 |
| | Case History 9: Mining. | 168 |
| | Case History 10: Power plant. | 170 |

| | |
|---|-----|
| Case History 11: Building services..... | 172 |
| Case History 12: Building services..... | 173 |
| Case History 13: Chemical industry..... | 175 |
| Case History 14: Food industry..... | 177 |

Appendix E

Drivers and Transmissions, 179

| | |
|--|-----|
| E.1 Electric Motor Efficiency | 179 |
| E.1.1 European Policies | 179 |
| E.1.2 North American Policies | 180 |
| E.1.3 Losses in Motors | 181 |
| E.1.4 Submersible Motor Efficiency | 182 |
| E.1.5 Energy Cost Calculation | 182 |
| E.1.6 Motors for Circulators in Heating Systems | 183 |
| E.1.7 Variable Frequency Drives | 184 |
| E.1.8 Repair or Replace? | 186 |
| E.2 Power Transmission | 187 |
| E.2.1 Efficiency and Characteristics of Various Types of Transmissions..... | 187 |
| E.2.2 Summary..... | 194 |

List of Figures

| | |
|---|-----|
| Typical LCC for a medium-sized industrial pumping system..... | xvi |
| 1.1 Manual calculation chart of LCC | 15 |
| 1.2 Example 4.1.b using the manual calculation chart | 16 |
| 2.1 Key cost components for a pumping installation as related to pipe size..... | 18 |
| 2.2 Typical pump performance and system curves – rotodynamic pumps | 19 |
| 2.3 Typical pump performance and system curves – positive displacement pumps..... | 19 |
| 2.4 Pump selection diagram for rotodynamic pumps with standard drivers handling clean liquids | 23 |
| 2.5 Average attainable industrial pump efficiency, η_{avg} , for rotodynamic volute pumps with closed impellers and for clean cold water (see Appendix C)..... | 24 |
| 2.6 Typical pump selection diagram for positive displacement pumps (PD pumps) | 25 |
| 2.7a Maximum attainable efficiencies for PD pumps with fluids below 100 mPa s | 26 |

| | | |
|------|---|----|
| 2.7b | Maximum attainable efficiencies for PD pumps with fluids below 1000 mPa s. | 27 |
| 2.8 | Indication of the influence of viscosity on the efficiency for different types of PD pumps | 28 |
| 2.9 | Example of a performance curve for a rotodynamic pump showing the preferred operating region | 29 |
| 2.10 | Variations in efficiency for a 30-kW 4-pole motor. | 38 |
| 2.11 | Efficiency curve of a typical variable frequency drive | 39 |
| 2.12 | Duration diagrams for two different pumping systems | 44 |
| 2.13 | System curve | 45 |
| 2.14 | Lines of constant efficiency (broken) superimposed over speed-regulated pump curves (solid) | 46 |
| 2.15 | The operating point on the reduced speed curve moves relatively higher on the pump curve as the speed is reduced | 46 |
| 2.16 | Example of specific energy as a function of static head and overall efficiency | 49 |
| 2.17 | Three different system curves A, B and C, all passing through the same duty point at full speed and the associated curves for specific energy. | 50 |
| 2.18 | Throttling a valve changes the rate of flow by adding pressure drop in the valve, thus moving the duty point along the pump curve | 51 |
| 2.19 | Compared with regulation by throttling, variable speed drives always save on energy. | 51 |
| 2.20 | Parallel pump operation | 52 |
| 2.21 | Reduced efficiency and head caused by leakage losses | 54 |
| 2.22 | Clearances from left to right: semi-open impeller clearance; closed impeller radial clearance; closed impeller axial clearance | 54 |
| 2.23 | Examples of clearances (s) in rotating positive displacement pumps: a) screw pump; b) gear pump | 58 |
| 2.24 | Pressure signals of a hydraulically acting diaphragm pump: a) healthy pressure signal; b) leakage in the hydraulic chamber (replenishing window [RW]) | 59 |
| 2.25 | Structure-borne noise signal and pressure signal of a reciprocating PD pump: a) healthy pump; b) leaking suction valve. | 59 |
| 2.26 | Preventive maintenance in terms of total maintenance costs. | 61 |

| | | |
|------|---|-----|
| 3.1 | Branched piping system showing the rate of flow in the various paths | 67 |
| 3.2 | Branched system showing the differential pressure in bar across the throttle valves needed to throttle the rate of flow to the set value | 68 |
| 3.3 | The branched piping system with flows balanced and pump impeller trimmed to eliminate excessive differential pressure across the control valves | 69 |
| 3.4 | The pump curve for the larger and smaller impeller trim; rate of flow for unbalanced flow is 166 m ³ /h (720 USgpm), balanced rate of flow 120 m ³ /h (520 USgpm) | 70 |
| 3.5 | Pressurized forced main system pumping down the sump using on/off control; evaluating changing pumping rate for lower operating costs | 71 |
| 3.6 | Total head as a function of rate of flow for the sump pump system | 73 |
| 3.7 | Pump curve for the pump selected for 30 m ³ /h | 74 |
| 3.8 | Sketch of pumping system in which the control valve fails | 76 |
| 3.9 | System resistance curve and pump curve showing the operation of the system | 77 |
| 3.10 | Pump curves and system curves showing the operation of the original system and the modified pump impeller | 77 |
| 4.1 | LCC comparison for the waste collection system | 82 |
| 4.2 | LCC comparison for the problem control valve system | 85 |
| 6.1 | New pumping system | 96 |
| 6.2 | Existing pump systems | 97 |
| A.1a | Operating duty point at $H_{\text{pump}} = H_{\text{syst}}$ for a rotodynamic pump | 106 |
| A.1b | Operating duty point at $H_{\text{pump}} = H_{\text{syst}}$ for a positive displacement pump | 106 |
| A.2 | Example of simple piping system | 107 |
| A.3 | System curve | 109 |
| A.4 | Piping systems with the same static head | 109 |
| A.5 | Piping system with $H_{\text{stat}} \approx 0$; $H_{\text{syst}} = H_j$ | 110 |
| A.6 | System with $H_j \approx 0$ | 110 |
| A.7 | Resultant pump curve for series operation | 111 |
| A.8 | Parallel pump operation | 111 |

| | | |
|------|--|-----|
| A.9 | Parallel operation of two similar pumps with different system curves. | 112 |
| A.10 | Pumping systems with different static heads | 112 |
| A.11 | System curve with varying static head | 113 |
| A.12 | Consequences of incorrectly calculated pipe losses | 114 |
| A.13 | The effect of deposits (scale, rust, etc.) on pipelines | 115 |
| A.14 | The effect of varying levels. | 116 |
| A.15 | The effect of adding margins to calculated system curve. | 116 |
| A.16 | Branched circulation system. | 118 |
| A.17 | Branched piping system, $H_{\text{stat}} = 0$ | 118 |
| A.18 | Branched pipe system with different static head | 119 |
| A.19 | Branched piping system with positive suction static head | 120 |
| A.20 | Pump performance by reduced impeller diameter | 121 |
| A.21 | Pump performance by variable speed | 122 |
| A.22 | Variable pitch propeller pumps. | 123 |
| A.23 | Mixed-flow pumps with adjustable inlet guide vanes | 123 |
| A.24 | Pump and system curves for more viscous liquids as compared with water. | 124 |
| A.25 | Pump and system curves for water and pulp suspension | 125 |
| B.1 | The duty point is the intersection between the pump and system curves: rotodynamic pump (RD); positive displacement pump (PD). | 128 |
| B.2 | Flow as a function of time – operating curve | 129 |
| B.3 | Duration curve of the flow. | 129 |
| B.4 | Graphical integration method to determine mean rates of flow | 130 |
| B.5 | Illustration of Equations B-1 and B-2 | 131 |
| B.6 | Control at (a) constant pressure, (b) constant flow, and (c) proportional level control | 135 |
| B.7 | Pump and drive system | 138 |
| B.8a | Examples of performance curves for a speed regulated rotodynamic pump | 139 |
| B.8b | Performance curves for PD-pumps with speed regulation | 139 |
| B.9 | Pump power requirement for speed-regulated rotodynamic pump with hydraulic coupling transmission | 140 |

| | | |
|------|--|-----|
| B.10 | Typical stroke adjustable drive element of a reciprocating positive displacement pump | 142 |
| B.11 | Power requirement for single stage rotodynamic pumps with flow control using various methods, in a system with a low ratio: H_{stat}/H_0 | 143 |
| C.1 | Typical single-stage, single-suction volute casing pump | 145 |
| C.2 | Maximum attainable efficiencies, η_{max} , of single-stage, single-suction volute casing pumps dependent on specific speeds and rates of flow | 147 |
| C.3 | Average attainable industrial pump efficiencies, η_{avg} , of single-stage, single-suction volute casing pumps dependent on specific speeds and rates of flow | 148 |
| E.1 | Losses in a typical 75 kW induction motor. | 181 |
| E.2 | Typical efficiencies of 2-pole, 3-phase asynchronous submersible motors | 182 |
| E.3 | Loading profile for a circulator | 183 |
| E.4 | (1) Uncontrolled circulators; (2) Circulators with voltage controlled motors; (3) Circulators with frequency controlled motors | 184 |

List of Tables

| | | |
|-----|---|-----|
| 1.1 | Factor C_p/C_n for a single cost element after n years. | 12 |
| 1.2 | Discount factor (df) for constant yearly expenditures | 13 |
| 2.1 | Control methods – applications and limitations. | 21 |
| 2.2 | Application ranges of positive displacement pumps | 33 |
| 2.3 | Properties of commercially available PD pumps; PH/PS = hydraulic power /shaft power | 34 |
| 2.4 | Positive and negative aspects of specific transmissions. | 43 |
| 3.1 | Operation and annual operating cost of the three-branched piping system in the various operating modes | 70 |
| 3.2 | Work sheets (a) and (b) showing how the rate of flow is calculated by pumping down and filling a sump | 72 |
| 3.3 | Cost comparison for energy cost for the 60 m ³ /h (260 USgpm) and 30 m ³ /h (130 USgpm) pumps | 75 |
| 3.4 | Cost comparison for Options A through D in the system with a failing control valve. | 78 |
| B.1 | Control methods – applications and limitations. | 132 |

| | |
|---|-----|
| B.2 Some control parameters used for pumps | 134 |
| D.1 Summary of Case Histories | 150 |
| E.1 Positive and negative aspects of specific transmissions | 194 |