

# Contents

12	Rotodynamic centrifugal slurry pumps . . . . .	1
12.1	Introduction. . . . .	1
12.1.1	Scope . . . . .	1
12.1.2	Purpose . . . . .	1
12.1.3	Pump types and nomenclature. . . . .	1
12.1.4	Definition of slurry . . . . .	2
12.1.5	Definition of slurry pumps. . . . .	2
12.1.6	Overhung impeller . . . . .	3
12.1.7	Frame mounted . . . . .	3
12.1.8	Cantilevered wet pit . . . . .	3
12.1.9	Submersible . . . . .	3
12.1.10	Lined type. . . . .	4
12.1.11	Unlined type . . . . .	4
12.1.12	Construction drawings . . . . .	4
12.1.13	Part names. . . . .	4
12.1.14	Letter dimensional designations. . . . .	27
12.2	Definitions. . . . .	31
12.2.1	Rate of flow ( $Q$ ) . . . . .	33
12.2.2	Speed ( $n$ ) . . . . .	33
12.2.3	Head ( $h$ ) - general term . . . . .	33
12.2.4	Condition points . . . . .	35
12.2.5	Suction conditions . . . . .	35
12.2.6	Power . . . . .	36
12.2.7	Pump pressures. . . . .	37
12.2.8	Mechanical seal terms . . . . .	37
12.2.9	Slurry terminology . . . . .	38
12.3	Design and application. . . . .	44
12.3.1	Scope . . . . .	44
12.3.2	Slurry services . . . . .	44
12.3.3	Froth pumping . . . . .	54
12.3.4	Wear in centrifugal slurry pumps . . . . .	58
12.3.5	Hydraulic design and application considerations . . . . .	63
12.3.6	Slurry system design . . . . .	64
12.3.7	Wetted materials of construction . . . . .	65
12.3.8	General arrangement details . . . . .	68
12.3.9	Drive train arrangements . . . . .	85
12.4	Installation, operation, and maintenance . . . . .	86
12.4.1	Installation . . . . .	86
12.4.2	Nozzle loads. . . . .	86
12.4.3	Connecting piping. . . . .	91
12.4.4	Commissioning. . . . .	92
12.4.5	Start-up . . . . .	92
12.4.6	Storage of elastomer linings. . . . .	92
12.4.7	Impeller removal. . . . .	92
12.4.8	Axial adjustment of the bearing housing . . . . .	92
12.4.9	Piping system design . . . . .	92
12.4.10	Possible operating problems . . . . .	93
12.4.11	Spare parts stock. . . . .	95
12.4.12	Maintenance procedures for maximum part life . . . . .	95
12.4.13	Operational considerations. . . . .	96

12.5	Intentionally left blank . . . . .	96
12.6	Testing . . . . .	96
12.6.1	Scope . . . . .	96
12.6.2	Test conditions . . . . .	97
12.6.3	Manufacturer’s testing . . . . .	97
12.6.4	Field tests . . . . .	97
12.6.5	Wear tests . . . . .	97
12.6.6	Instrumentation . . . . .	98
Appendix A	Equipment data sheets (informative) . . . . .	99
Appendix B	Nozzle loads tables (informative) . . . . .	104
Appendix C	Materials data (informative) . . . . .	106
Appendix D	Source material and references (informative) . . . . .	109
Appendix E	Index (informative) . . . . .	113
Figures		
12.1.3	– Rotodynamic centrifugal slurry pump types . . . . .	2
12.1.5	– Typical material types and discharge pressure for particle size. . . . .	3
12.1.13a	– Overhung impeller, separately coupled, single stage, frame mounted, metal-lined pump (OH0) . . . . .	5
12.1.13b	– Overhung impeller, separately coupled, single stage, frame mounted, elastomer-lined pump (OH0) . . . . .	6
12.1.13c	– Overhung impeller, separately coupled, single stage, frame mounted, elastomer-lined pump, adjustable sideliners (OH0) . . . . .	7
12.1.13d	– Overhung impeller, separately coupled, single stage, frame mounted, end suction, vulcanized-elastomer-lined pump (OH0) . . . . .	8
12.1.13e	– Overhung impeller, separately coupled, single stage, frame mounted, end suction, metal, unlined casing pump (OH0) . . . . .	9
12.1.13f	– Overhung impeller, separately coupled, single stage, frame mounted, side inlet, metal, unlined casing pump (OH0) . . . . .	10
12.1.13g	– Overhung impeller, separately coupled, single stage, frame mounted, end suction, metal, tie bolt plate construction pump (OH0) . . . . .	11
12.1.13h	– Overhung, open impeller, separately coupled, single stage, foot mounted, metal, ASME B73.1 type pump (OH1) . . . . .	12
12.1.13i	– Overhung impeller, separately coupled, single stage, wet pit cantilever, elastomer-lined, single suction pump (VS5) . . . . .	13
12.1.13j	– Overhung impeller, separately coupled, single stage, wet pit cantilever, elastomer, vulcanized-lined, double suction pump (VS5) . . . . .	14
12.1.13k	– Overhung impeller, separately coupled, single stage, wet pit cantilever, unlined, metal, single suction pump (VS5) . . . . .	15
12.1.13l	– Overhung impeller, close coupled, single stage, submersible, elastomer-coated, single suction pump (OH8B) . . . . .	16
12.1.13m	– Overhung impeller, close coupled, single stage, submersible, elastomer-lined, single suction pump (OH8B) . . . . .	17

12.1.13n – Overhung impeller, close coupled, single stage, submersible, elastomer-lined, double suction pump (OH8B) . . . . .	18
12.1.13o – Overhung impeller, close coupled, single stage, end suction, metal, submersible pump with agitator (OH8B) . . . . .	19
12.1.13p – Overhung impeller, close coupled, single stage, submersible, metal, double suction pump (OH8B) . . . . .	20
12.1.14a – Horizontal pump dimensions . . . . .	28
12.1.14b – Direct drive pump and motor assembly dimensions . . . . .	29
12.1.14c – Vertical pump dimensions . . . . .	30
12.2.3.4 – Datum elevations for various slurry pump designs . . . . .	34
12.3.2.1 – Solids transport rate . . . . .	46
12.3.2.2 – Nomograph for the relationship of concentration to specific gravity in aqueous slurries . . . . .	47
12.3.2.3 – Schematic classification of slurries in industrial pipeline applications . . . . .	48
12.3.2.4 – Nomograph for maximum velocity at limit of stationary deposition of solids. . . . .	49
12.3.2.5 – Effect of settling slurry on pump characteristics (schematic) . . . . .	51
12.3.2.7 – Effect of average particle size and impeller diameter on $H_r$ and $R_h$ (For solids concentration by volume, $C_v = 15\%$ with solids $S_s = 2.65$ and a negligible amount of fine particles. Impeller diameters are given in millimeters and inches.) . . . . .	52
12.3.3.2 – Application of empirical froth factor . . . . .	56
12.3.3.3 – Approximate correlation between empirical froth factor (FF) and experimental froth volume factor (FVF) for froth pumps with increased inlet size . . . . .	57
12.3.4.1a – Sliding wear coefficient $W_c$ for different resisting materials in a neutral pH media for different average-sized, silica based, abrading particles . . . . .	59
12.3.4.1b – Erosion response for different impingement angles and materials. . . . .	60
12.3.4.2a – Service class chart for slurry pump erosive wear. . . . .	62
12.3.4.2b – Miller number versus material abrasivity . . . . .	62
12.3.6 – Typical constant concentration slurry pipeline friction loss characteristics . . . . .	65
12.3.8.2a – Typical lip seal and its components . . . . .	69
12.3.8.2b – Typical labyrinth seal. . . . .	70
12.3.8.2c – Generic bearing isolator and its major components . . . . .	70
12.3.8.3.1a – “Flush-type” stuffing box with lantern ring in standard position . . . . .	72
12.3.8.3.1b – “Weep-type” stuffing box with lantern ring . . . . .	72
12.3.8.3.1c – Flow through flush . . . . .	73
12.3.8.3.6 – Centrifugal (dynamic) seal with “dry-type” packing . . . . .	75
12.3.8.3.7 – Multiple elements lip seal with internal flush . . . . .	76
12.3.8.3.8a – Flow rates required to create 4.6 m/s (15 ft/s) velocity past a bushing . . . . .	78
12.3.8.3.8b – Slurry pump shaft alignment and runout . . . . .	79
12.3.8.3.8c – Dual back-to-back pressurized seal arrangement for high pressure slurry applications . . . . .	80
12.3.8.3.8d – Typical face-to-back dual pressurized seal arrangement for slurry applications . . . . .	80

12.3.8.3.9a – Rotating elastomeric bellows seal . . . . .	81
12.3.8.3.9b – Stationary elastomeric bellows seal . . . . .	81
12.3.8.3.9c – Heavy-duty slurry seal with quench device . . . . .	82
12.3.8.3.9d – Heavy-duty slurry seal with elastomeric liner . . . . .	82
12.3.8.3.9e – Fully split nonpusher seal . . . . .	83
12.3.8.9f – Fully split pusher seal . . . . .	83
12.3.8.3.9g – Specialty slurry seal . . . . .	83
12.4.2 – Direction of forces and moments being applied to suction and discharge nozzles . . . . .	86
12.4.2.7a – Sliding movement when forces and moments are transferred to pump feet. . . . .	88
12.4.2.7b – Forces and moments applied to pumps with various suction and discharge nozzle locations. . . . .	89
12.4.2.9 – Bolts in tension when a moment is applied to the pump . . . . .	91
Tables	
12.1.13a — Slurry pump nomenclature – alphabetical listing . . . . .	21
12.1.13b – Slurry pump nomenclature — numerical listing. . . . .	26
12.2a — Principal symbols . . . . .	31
12.2b — Subscripts . . . . .	32
12.3.2.7 — Specific gravity correction factor . . . . .	52
12.3.3.2 — Approximate froth factors . . . . .	55
12.3.5a — Recommended service limitations for acceptable wear. . . . .	63
12.3.5b — Acceptable range of relative flow rates for slurry pump casing optimum wear . . . . .	64
12.3.7.1 — General suitability of wetted materials . . . . .	66
12.3.8.2 — Calculated fatigue life of bearings by slurry service class. . . . .	71
12.3.8.3.8 — Application limits of single mechanical seals . . . . .	77
12.3.8.3.10 — Recommended water quality limits . . . . .	84
12.4.2.9 — Calculation of allowable forces and moments on the suction(s) and discharge(d) connections. . . . .	90
B.1 – Typical allowable combined nozzle loads for centrifugal end-suction slurry pumps – metric . . . . .	104
B.2 – Typical allowable combined nozzle loads for centrifugal end-suction slurry pumps – US customary units. . . . .	105