

Contents

	Page
Foreword.....	vii
40.6 Methods for rotodynamic pump efficiency testing.....	1
40.6.1 Scope	1
40.6.1.1 Introduction.....	1
40.6.2 Terms and definitions	1
40.6.2.1 Lists of symbols and subscripts.....	5
40.6.3 Pump efficiency testing.....	6
40.6.3.1 General.....	7
40.6.3.2 Measurement uncertainty	7
40.6.4 Considerations when determining the efficiency of certain pumps	9
40.6.4.1 Vertically suspended pumps.....	9
40.6.4.2 Submersible pumps.....	9
40.6.4.3 All other pump types	9
40.6.4.4 Determination of pump overall efficiency	10
40.6.5 Test procedures.....	10
40.6.5.1 General.....	10
40.6.5.2 Testing equipment.....	10
40.6.5.3 Test report	10
40.6.5.4 Test arrangements	10
40.6.5.5 Test conditions	10
40.6.6 Analysis	11
40.6.6.1 Translation of the test results to the specified speed of rotation (n_{sp})	11
40.6.6.2 Pump efficiency	11
40.6.6.3 Performance curve	12
Appendix A Test arrangements (normative)	13
A.1 General.....	13
A.2 Measurement principles to determine pump total head.....	13
A.3 Various methods to determine pump total head	13
A.4 Pumps tested with fittings	17
A.5 Pumping installation under submerged conditions	17
A.6 Friction losses at inlet and outlet	18
Appendix B Reporting of test results (informative)	21
B.1 DOE certification reports.....	21
Appendix C Measurement equipment (normative).....	22
C.1 Measurement of head.....	22
C.2 Measurement of rotating speed	22
C.3 Measurement of flow rate	23
C.4 Measurement of pump, driver, or control power input	24
C.5 Temperature	26
Appendix D Suitable time periods for calibration of test instruments (normative)	27
D.1 Recalibration interval	27
Appendix E Appendix E (normative)	28
E.1 Scope	28
E.2 Circulator Specific Testing Requirements.....	28
E.3 Testing Exceptions and Modifications for Circulator Pumps	28
Appendix F Unit conversions (informative)	29

Appendix G	DOE compared to HI 40.6 nomenclature	31
Appendix H	Determination, application, and calculation of instrument (systematic) uncertainty (informative).....	32
H.1	Determination, application, and calculation of instrument (systematic) uncertainty	32
H.2	Distribution of probability.....	33
H.3	Examples of measurement uncertainty calculations	34
Appendix I	References	44
Appendix J	Index	47
Figures		
A.1	— Determination of pump head	14
A.2	— Outlet pressure tapping	16
A.3	— Requirements for static pressure tap	16
A.4	— One pressure tapping (minimum requirement)	16
A.5	— Bowl assembly total head determination for vertically suspended pumps	19
A.6	— Bowl assembly total head determination for vertically suspended pump with a closed suction	20
C.1	— Arrangement for determination of reference plane of spring pressure gauges.....	22
H.1	— Output signal vs. pressure value	40
Tables		
40.6.2	— List of quantities, terms, and definitions	2
40.6.2.1a	— List of symbols	5
40.6.2.1b	— List of subscripts.....	6
40.6.3.2.2	— Permissible amplitude of fluctuation as a percentage of mean value of quantity being measured at any test point.....	7
40.6.3.2.3	— Maximum permissible measurement device uncertainty.....	8
D.1	— Instrument recalibration maximum intervals	27
F.1	— Conversion factors	29
G.1	— Comparison of equivalent nomenclature	31
H.1	— Lab pressure calibrator calibration data.....	35
H.2	— Published accuracy of lab calibration devices	35
H.3	— Lab precision DC current measurement device calibration data	36
H.4	— Lab DC current source calibration data.....	36
H.5	— Pressure transducer calibration.....	37
H.6	— DA system current measurement module (output) calibration data.....	37
H.7	— Calculation of percent uncertainty for the discharge pressure, full system of 300 psi pressure transducer and data acquisition system	39
H.8	— Differential pressure transducer information.....	40
H.9	— Signal measurement device information.....	40
H.10	— Venturi information - BIF 2-in s/n 12345	40
H.11	— Differential pressure transducer calibration data	41
H.12	— Differential pressure transducer calibration data analysis	41
H.13	— Venturi flowmeter calibration data and analysis	42
H.14	— Calculation of individual device uncertainty and total uncertainty.....	42