

Contents

Page

Foreword	ix
9.6.5 Rotodynamic Pumps for Condition Monitoring	1
9.6.5.1 Introduction.	1
9.6.5.1.1 Scope	1
9.6.5.1.2 Purpose	1
9.6.5.1.3 Use of this document	1
9.6.5.2 Monitoring Strategies	3
9.6.5.2.1 Monitoring frequency	3
9.6.5.2.2 Control limits.	3
9.6.5.2.2.1 Alert limit settings.	3
9.6.5.2.2.2 Alarm limit settings.	4
9.6.5.2.2.3 Shutdown limit settings.	4
9.6.5.2.2.4 Definition of baseline used in alarm set point limits	4
9.6.5.2.2.5 Definition of field acceptance level or industry standard level	4
9.6.5.3 Power monitoring	4
9.6.5.3.1 Introduction.	4
9.6.5.3.2 Means of power monitoring	5
9.6.5.3.3 Power monitoring frequency.	6
9.6.5.3.4 Power control limits	6
9.6.5.4 Temperature monitoring	6
9.6.5.4.1 Introduction.	6
9.6.5.4.2 Means of monitoring temperature	6
9.6.5.4.3 Specific applications of temperature monitoring.	6
9.6.5.4.3.1 Motor-winding temperature	6
9.6.5.4.3.2 Temperature-sensitive liquids.	6
9.6.5.4.3.3 Rolling element bearing temperatures	7
9.6.5.4.3.4 Liquid-film bearing and seal faces temperatures	7
9.6.5.4.3.5 Pumped liquid temperature rise	7
9.6.5.4.4 Sealless pump liquid temperature	7
9.6.5.4.4.1 Sealless pump temperature damage	7
9.6.5.4.5 Temperature monitoring frequency.	8
9.6.5.4.6 Temperature control limits	8
9.6.5.5 Corrosion monitoring	8
9.6.5.5.1 Introduction.	8
9.6.5.5.2 Means of corrosion monitoring.	8
9.6.5.5.2.1 Corrosion monitoring by visual/dimensional inspection	8

9.6.5.5.2.2	Corrosion by electrical resistance (ER)	9
9.6.5.5.2.3	Corrosion by linear polarization resistance (LPR)	9
9.6.5.5.2.4	Corrosion by ultrasonic thickness measurement (UTM).	9
9.6.5.5.3	Corrosion monitoring frequency	9
9.6.5.5.4	Corrosion parameter control limits	9
9.6.5.6	Leakage monitoring	10
9.6.5.6.1	Introduction.	10
9.6.5.6.2	Means of monitoring leakage	10
9.6.5.6.2.1	Leakage by visual inspection	10
9.6.5.6.2.2	Leakage by organic vapor analyzer (OVA) inspection	10
9.6.5.6.2.3	Seal leakage in submersible pumps.	10
9.6.5.6.2.4	Leakage in an inner seal of dual unpressurized seal arrangements	11
9.6.5.6.2.5	Leakage in an inner seal of dual pressurized seal arrangements	11
9.6.5.6.2.6	Double-walled system	11
9.6.5.6.3	Leakage monitoring frequency.	12
9.6.5.6.4	Leakage control limits.	12
9.6.5.7	Pressure monitoring	13
9.6.5.7.1	Introduction.	13
9.6.5.7.2	Means of pressure monitoring	13
9.6.5.7.3	Pressure monitoring frequency	13
9.6.5.7.4	Pressure control limits	14
9.6.5.8	Vibration monitoring	14
9.6.5.8.1	Introduction.	14
9.6.5.8.2	Means of vibration monitoring	15
9.6.5.8.3	Vibration monitoring frequency.	15
9.6.5.8.4	Vibration control limits	15
9.6.5.9	Lubricant analysis.	16
9.6.5.9.1	Introduction.	16
9.6.5.9.2	Measuring metal particles from wear	16
9.6.5.9.2.1	Evaluating wear rates	17
9.6.5.9.3	Measuring contamination of lubricant	17
9.6.5.9.3.1	Organic contamination of lubricant.	17
9.6.5.9.3.2	Inorganic contamination of lubricant.	17
9.6.5.9.4	Measuring lubricant degradation	18
9.6.5.9.5	Lubricant sampling techniques.	18
9.6.5.9.6	Lubricant monitoring frequency	18
9.6.5.9.7	Lubricant control limits	18

9.6.5.10	Shaft position monitoring	18
9.6.5.10.1	Introduction.	18
9.6.5.10.2	How to monitor shaft position	19
9.6.5.10.3	Shaft monitoring frequency	19
9.6.5.10.4	Shaft control limits	19
9.6.5.11	Rate-of-flow monitoring	19
9.6.5.11.1	Introduction.	19
9.6.5.11.2	Measuring rate of flow	19
9.6.5.11.3	Rate-of-flow monitoring frequency	19
9.6.5.11.4	Rate-of-flow control limits	19
9.6.5.12	Rotational speed (rpm) monitoring.	20
9.6.5.12.1	Introduction.	20
9.6.5.12.2	Speed measurement methods	20
9.6.5.12.3	Speed monitoring frequency	20
9.6.5.12.4	Speed control limits	20
9.6.5.13	Bearing wear monitoring of plain bearings in sealless pumps	20
9.6.5.13.1	Introduction.	20
9.6.5.13.2	Means of detecting bearing wear	20
9.6.5.13.2.1	Bearing materials	20
9.6.5.13.2.2	Bearing wear detection methods	21
9.6.5.13.3	Bearing wear monitoring frequency	22
9.6.5.13.4	Bearing wear control limits	22
9.6.5.14	System and pump design review	22
9.6.5.14.1	Introduction.	22
9.6.5.14.2	Design review practice	22
9.6.5.14.2.1	Mechanical application review	22
9.6.5.14.2.2	Hydraulic application review	22
9.6.5.14.2.3	Installation review	23
9.6.5.14.2.4	Operating procedures review	24
9.6.5.14.3	Design review frequency	24
9.6.5.15	Maintenance inspection	24
9.6.5.15.1	Introduction.	24
9.6.5.15.2	Maintenance inspection practice	25
9.6.5.15.2.1	Maintenance inspection of keys and keyways	25
9.6.5.15.2.2	Maintenance inspection of coupling flexible elements	25
9.6.5.15.2.3	Maintenance inspection for shaft bending fatigue	26
9.6.5.15.2.4	Maintenance inspection for shaft torsional fatigue	26
9.6.5.15.2.5	Maintenance inspection for torsional overload	26

9.6.5.15.2.6	Maintenance inspection for impeller fatigue/breakage	26
9.6.5.15.2.7	Maintenance inspection for erosion wear from the action of flow, abrasion, and/or corrosion	26
9.6.5.15.2.8	Maintenance inspection for cavitation erosion	27
9.6.5.15.2.9	Maintenance inspection for hydraulic performance	27
9.6.5.15.3	Maintenance inspection frequency.	27
9.6.5.16	Wireless data transmission technology	27
9.6.5.16.1	CBM: transmission schemes for wireless systems.	27
9.6.5.16.2	Wireless communication for CBM sensor systems	28
9.6.5.16.3	Wireless communication standards	29
References	29
Appendix A	Condition monitoring, failure modes.	30
Appendix B	Condition monitoring indicators	36
Appendix C	Vibration analysis	41
Appendix D	Condition-based maintenance	51
Appendix E	Preinstallation hydrostatic test	54
Appendix F	Definitions.	55
Appendix G	Condition Monitoring as a Tool for Asset Reliability Management	57
Appendix H	Index.	59
Figures		
9.6.5.1.3	— Typical P-F interval curves	1
9.6.5.16.1	— Example of a Vibration Diagnostic System Network (star topology)	28
C.1	— Typical vibration waveform	42
C.2	— Typical waveform over time.	42
C.3	— Example of ski slope spectral signature	43
C.4	— High-frequency spectral signature	43
C.5	— 1× running speed spike due to imbalance – dynamic.	43
C.6	— 1× running speed spike due to imbalance – overhung	44
C.7	— 1× running speed spike due to imbalance – vertical pump	44
C.8	— Vibration spike due to eccentric sheaves	45
C.9	— Misaligned sheaves	45
C.10	— Belt resonance	45
C.11	— Bent shaft	46
C.12	— Parallel misalignment	46

C.13 — Angular misalignment	47
C.14 — Severe misalignment	47
C.15 — Cocked bearing	47
C.16 — Rotating looseness	48
C.17 — Structural looseness	48
C.18 — Bearing wear	49
C.19 — Natural frequencies of bearing system	49
C.20 — Bearing race flaw	49
C.21 — Bearing – ball or roller damage	50
C.22 — Bearings – severely damaged	50
D.1 — Summary of condition-based monitoring (CBM) strategies	51
Tables	
9.6.5.1.3 — Asset reliability management strategies	2
9.6.5.6.2.6 — Application guidelines for leakage monitoring systems' mechanical seals	12
9.6.5.8.4 — Recommended vibration control limits	16
A.1 — Condition monitoring failure modes	30
A.2 — Additional failure modes for sealless pumps and pumps with journal bearings	35
B.1 — Condition monitoring indicators	36