

Contents

Page

Foreword	vii
Flowchart for use of standard (mechanical considerations)	x
Flowchart for use of standard (hydraulic considerations)	xi
9.6.6 Rotodynamic pumps for pump piping	1
9.6.6.1 Introduction	1
9.6.6.1.1 Purpose	1
9.6.6.1.2 Scope	1
9.6.6.1.2.1 Piping	1
9.6.6.1.2.2 Viscosity considerations	1
9.6.6.2 Pump Piping Design General	2
9.6.6.3 Inlet (suction) piping requirements	3
9.6.6.3.2 Inlet (suction) pipe size/velocity requirements	4
9.6.6.3.3 Effect of piping-generated swirl	5
9.6.6.3.4 Required straight pipe lengths	5
9.6.6.3.5 Need for physical hydraulic model study	12
9.6.6.3.6 Use of computational fluid dynamics (CFD)	13
9.6.6.3.6.1 Acceptable uses of CFD modeling in pump suction hydraulics	14
9.6.6.3.6.2 Unacceptable uses of CFD modeling in pump suction hydraulics	14
9.6.6.3.7 Pump suction piping/wet-well connection	14
9.6.6.3.8 Pump suction elbows	15
9.6.6.3.9 Pump station retrofit or modification	16
9.6.6.4 Outlet (discharge) piping requirements	16
9.6.6.4.1 Pipe size/velocity requirements	16
9.6.6.4.2 Outlet (discharge) straight pipe lengths	17
9.6.6.4.3 Recommended valves	17
9.6.6.4.3.1 Shut-off/Isolation valves	17
9.6.6.4.3.2 Check valves	17
9.6.6.4.3.3 Pump control valves	18
9.6.6.4.3.4 Triple-duty valves	18
9.6.6.4.3.5 Air release valves	19
9.6.6.4.4 Water hammer	19

9.6.6.5	Inlet (suction) and outlet (discharge) general piping requirements	20
9.6.6.5.1	Pipe nozzle alignment/pipe expansion load	20
9.6.6.5.1.1	Pump nozzle analysis	20
9.6.6.5.2	Pipe supports/anchors	21
9.6.6.5.2.2	Design considerations	22
9.6.6.5.2.3	Cold spring	22
9.6.6.5.2.4	Final installation	22
9.6.6.5.2.5	Field adjustment	23
9.6.6.5.3	Parallel operation	23
Appendices	Introduction	26
Appendix A	System curves	27
A.1	Calculation of the system curve	27
A.2	Pipe head loss calculation methods	28
Appendix B	Water hammer	30
B.1	Water hammer	30
Appendix C	Selecting and locating pipe supports and restraints	34
C.1	Restraint and stops	34
C.2	Pipe supports for vertical loads	34
C.3	Guides and restraints	35
C.4	True anchors	36
C.5	Spring supports	36
C.6	Friction from supports	37
Appendix D	Expansion joints	38
D.1	Expansion joint types	38
D.2	Expansion joint application	40
Appendix E	Specialty piping components and applications	42
E.1	Check valves and strainers	42
E.2	Devices to improve flow to the pump	44
E.3	Piping for suction lift applications	49
E.4	Solids/slurry	49
E.5	Air valves	50
Appendix F	Pressure pulsation and acoustic resonance	52
F.1	General	52
F.2	Piping acoustics	52
Appendix G	Modifications or improvements to non-conforming existing systems	54
G.1	Introduction	54
G.2	In-Kind Replacement	54

G.3	Assessment of Non-Compliant Piping	55
G.4	Mitigation of Non-Compliant Piping	55
Appendix H	References	56
Appendix I	Sources of additional information	58
Appendix J	List of acronyms	59

Figures

9.6.6.3	— Suction pipe design for systems with suction lift	4
9.6.6.3.4a	— General example of requirement 9.6.6.3.4.5 with eccentric reducer downstream of the suction pipe from above	6
9.6.6.3.4b	— General example – pump suction with a required L_2 length for a flow-disturbing fitting	8
9.6.6.3.4c	— General example – pump suction with an allowed fitting connected directly and a required L_2 length for a flow-disturbing fitting	8
9.6.6.3.4d	— Specific example – pump suction with a required L_2 length for a short-radius reducing elbow (< 30% area reduction)	8
9.6.6.3.4e	— Specific example – pump suction with a concentric reducer (1 pipe size reduction), and a required L_2 length for a short-radius elbow	9
9.6.6.3.4f	— Specific example – pump suction with a required L_2 length for a suction header (tee or branch flow)	9
9.6.6.3.4g	— Specific example – pump suction with an eccentric reducer (2 pipe size reduction), a required L_2 length for a concentric reducer (4 pipe size reduction), and a short-radius elbow	9
9.6.6.3.4h	— Specific example – pump suction with a required L_2 length for a concentric reducer (4 pipe size reduction) and a long-radius elbow	10
9.6.6.3.4i	— Specific example – pump suction with a manufacturer-approved 90° elbow, an eccentric reducer (1 pipe size reduction), and a required L_2 length for long-radius elbow	10
9.6.6.3.4j	— Specific example – pump suction with a manufacturer-approved 90° elbow and a required L_2 length for an eccentric reducer (4 pipe size reduction)	10
9.6.6.3.4k	— Specific example (top view) – between bearing split case (double suction) pump with an eccentric reducer (1 pipe size reduction), a required L_2 length for a concentric reducer (4 pipe size reduction), and a short-radius elbow (*added one diameter for double suction with elbow in plane with pump shaft)	11
9.6.6.3.4l	— Undesirable effect of an elbow mounted directly on suction nozzle of double suction pump with flow direction into the elbow inlet parallel to the shaft (applies to all double suction applications with either horizontal or vertical shaft orientation on either side or bottom suction)	11
9.6.6.3.4m	— Examples of suction pipe fittings near the pump that require approval of the pump manufacturer	12
9.6.6.4.3	— Triple-duty valve	19
9.6.6.5.3a	— Minimum required suction pipe length and spacing for parallel pumps	24
9.6.6.5.3b	— Parallel pump installation L_2	24
9.6.6.5.3c	— Constant-velocity manifold design, parallel pumps	25
9.6.6.5.3d	— Alternatives for suction header to suction lateral transition	25
C.1	— Pipe supports for vertical loads	35
C.2	— Solid pipe hanger supports	35

C.3 — Constant-effort spring supports	35
C.4 — Pipe guides	36
C.5 — Spring supports	37
D.1 — Slip/packing expansion joint	38
D.2 — Rubber expansion joints	39
D.3 — Metal bellows expansion joint	39
D.4 — Expansion joint bolting arrangement.	40
E.1 — Foot valve and screen.	43
E.2 — Foot valve (rubber flapper check valve without screen)	43
E.3 — Foot valve installation	43
E.4 — Typical temporary strainer.	44
E.5 — Second upstream perpendicular elbow.	44
E.6 — Straightening vanes	45
E.7 — Straightening vanes downstream from bend.	46
E.8 — Straightening vanes for solids-bearing liquids.	47
E.9 — Turning vanes	48
E.10 — Grating or flow grid	48
E.11 — Self-priming piping arrangement.	49
 Tables	
9.6.6.3.4 — Minimum required straight pipe length (L_2) before pump suction nozzle	7
B.1 — Magnitude of pressure	32